

August 27, 2020

Mr. Brandon L. Phillips, Engineering Associate
Solid Waste Permitting and Monitoring Section
Division of Mining and Solid Waste Management
Bureau of Land and Waste Management
South Carolina Department of Health and Environmental Control
2600 Bull Street
Columbia, South Carolina 29201



AUG 27 2020

DIVISION OF MINING SOLID WASTE MANAGEMENT BLWM

RE: Permit Application for the Greenpointe Class

Two Construction, Demolition, and Land-Clearing Debris (C&D) Landfill Expansion

Permit No.: LF2-00001 Project No.: 16227-0004

Dear Mr. Phillips:

In response to your comments via email on August 14, 2020 for the referenced project, we have the following comment response. The following items were brought to our attention in the aforementioned email and are listed along with our response to each item:

FOLLOW-UP REVIEW COMMENTS BY STORMWATER SECTION:

- 1. Line item 17 from the review comments response letter still needs to be corrected. Basin 1 lists the riser crest length as 16.5' in the hydrology report, Basin 2 lists 16.0' (which is correct with the drawings which also show 16.0'), and Basin 3 15.0' in the hydrology report. The HydroCad report needs to be updated for Basins 1 and 3 to match the Construction Plans.
 - The riser crest lengths for Basins 1, 2, & 3 in the Post-Development Hydraflow Report match the Outlet Control Structure Details shown on Sheet C8.1 of the Construction Plans (DWG No. 01,1168-D21 dated August 20, 2020). The Post-Development Hydraflow Report and Sheet C8.1 have been enclosed for your reference.
- 2. Line item 18 the Surface Water Protection Plan needs to be added to the Construction Plans in addition to it being added to the SWPPP.
 - Sheet C7.1 of the Construction Plans (DWG No. 01,168-D21 dated August 20, 2020) have been updated to include the Surface Water Protection Plan Construction Sequence.

Mr. Brandon Phillips, Engineering Associate South Carolina Department of Health and Environmental Control August 27, 2020 - Page 2 of 2

We trust that this information is to your satisfaction and look forward to your approval. If you have any questions or comments, please contact us at (803) 779-2078.

Very truly yours,

ALLIANCE CONSULTING ENGINEERS, INC.

Ryan T. Ohmer, P.E. Project Engineer

Enclosures

cc: Mr. Radford Jenkins, Wasteco, Inc.

Mr. Robert "Ty" Hawkins, Bunnell Lammons Engineering

Mr. Deepal S. Eliatamby, P.E., SCCED, Alliance Consulting Engineers, Inc.


Mr. Kyle M. Clampitt, P.E., Alliance Consulting Engineers, Inc. Mr. Gregory T. Farrell, P.E., Alliance Consulting Engineers, Inc.

Hydrograph Return Period Recap Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

	Hydrograph	Inflow				Hydrograph					
lo.	type (origin)	hyd(s)	1-yr	2-yr	3-yr	5-yr	10-yr	25-yr	50-yr	100-yr	Description
1	SCS Runoff			63.15			110.65	138.14		207.53	DA 1.1
2	Reservoir	1		1.068			1.188	2.475		37.79	Thru Detention Basin#1
3	SCS Runoff			82.22			146.12	183.24		277.06	DA 2.1
4	SCS Runoff			100.56			176.19	219.96		330.44	DA 1.2
5	Reservoir	4		1.870			2.051	3.631		36.40	Thru Detention Basin#2
6	SCS Runoff			9.445			31.88	47.26		91.39	DA BYPASS 2.1
7	Reservoir	3		1.575			6.338	18.35		159.03	Thru Detention Basin#3
8	Combine	6, 7		10.95			33.61	61.80		246.41	Outfall 2
9	Combine	2, 5,		2.938			3.541	7.168		72.26	Outfall 1

Proj. file: Post-Development Hydraflow.gpw

Thursday, 06 / 25 / 2020



<u>Legend</u>

<u>Hyd.</u>	<u>Origin</u>	Description
1	SCS Runoff	DA 1.1
2	Reservoir	Thru Detention Basin#1
3	SCS Runoff	DA 2.1
4	SCS Runoff	DA 1.2
5	Reservoir	Thru Detention Basin#2
6	SCS Runoff	DA BYPASS 2.1
7	Reservoir	Thru Detention Basin#3
8	Combine	Outfall 2
9	Combine	Outfall 1

Project: Post-Development Hydraflow.gpw

Thursday, 06 / 25 / 2020


Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 1

DA 1.1

= SCS Runoff Peak discharge = 63.15 cfsHydrograph type Storm frequency Time to peak $= 716 \, \text{min}$ = 2 yrsTime interval = 2 min Hyd. volume = 129.060 cuft = 17.340 acCurve number = 86 Drainage area Basin Slope = 0.0 % Hydraulic length = 0 ftTc method Time of conc. (Tc) $= 6.00 \, \text{min}$ = User Distribution = Type II Total precip. = 3.60 inShape factor = 484 Storm duration = 24 hrs



Hydrograph Summary Report Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	SCS Runoff	63.15	2	716	129,060				DA 1.1
2	Reservoir	1.068	2	1018	129,090	1	807.19	83,113	Thru Detention Basin#1
3	SCS Runoff	82.22	2	716	167,383				DA 2.1
4	SCS Runoff	100.56	2	716	205,499				DA 1.2
5	Reservoir	1.870	2	966	205,540	4	802.40	128,308	Thru Detention Basin#2
6	SCS Runoff	9.445	2	726	39,077				DA BYPASS 2.1
7	Reservoir	1.575	2	962	167,392	3	806.09	104,267	Thru Detention Basin#3
8	Combine	10.95	2	726	206,469	6, 7			Outfall 2
9	Combine	2.938	2	986	334,630	2, 5,			Outfall 1
Post	t-Developmer	nt Hydrafl	ow.gpw		Return Pe	eriod: 2 Ye	ar	Thursday 0	06 / 25 / 2020
Pos	-Developmer	nt Hydraii	ow.gpw		Return Pe	eriod: 2 Ye	ar	Thursday, 0	06 / 25 / 2020

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Pond No. 1 - Detention Basin #1

Pond Data

Contours -User-defined contour areas. Conic method used for volume calculation. Begining Elevation = 803.00 ft

Stage / Storage Table


Stage (ft)	Elevation (ft)	Contour area (sqft)	Incr. Storage (cuft)	Total storage (cuft)
0.00	803.00	00	0	0
0.01	803.01	100	0	0
1.00	804.00	13,933	5,020	5,020
2.00	805.00	20,159	16,949	21,969
3.00	806.00	28,637	24,272	46,241
4.00	807.00	32,348	30,471	76,712
5.00	808.00	36,240	34,272	110,984
6.00	809.00	39,890	38,047	149,030
7.00	810.00	43,939	41,894	190,924
8.00	811.00	46,647	45,282	236,206
9.00	812.00	50,386	48,500	284,706
10.00	813.00	54,240	52,296	337,002
11.00	814.00	58,612	56,406	393,408
12.00	815.00	61,880	60,233	453,640

Culvert / Orifice Structures

Weir Structures

	[A]	[B]	[C]	[PrfRsr]		[A]	[B]	[C]	[D]
Rise (in)	= 24.00	3.00	0.00	0.00	Crest Len (ft)	= 16.50	24.00	1.50	0.00
Span (in)	= 24.00	3.00	0.00	0.00	Crest El. (ft)	= 810.50	811.00	809.92	0.00
No. Barrels	= 1	1	0	0	Weir Coeff.	= 3.33	2.60	3.33	3.33
Invert El. (ft)	= 803.00	803.00	0.00	0.00	Weir Type	= 1	Broad	Rect	
Length (ft)	= 100.00	0.00	0.00	0.00	Multi-Stage	= Yes	No	Yes	No
Slope (%)	= 1.00	0.00	0.00	n/a					
N-Value	= .013	.013	.013	n/a					
Orifice Coeff.	= 0.60	0.60	0.60	0.60	Exfil.(in/hr)	= 0.000 (by	Contour)		
Multi-Stage	= n/a	Yes	No	No	TW Elev. (ft)	= 0.00			

Note: Culvert/Orifice outflows are analyzed under inlet (ic) and outlet (oc) control. Weir risers checked for orifice conditions (ic) and submergence (s).



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 2

Thru Detention Basin#1


Hydrograph type = Reservoir Storm frequency = 2 yrs Time interval = 2 min Inflow hyd. No. = 1 - DA 1.1

Reservoir name = Detention Basin #1

Peak discharge = 1.068 cfs
Time to peak = 1018 min
Hyd. volume = 129,090 cuft
Max. Elevation = 807.19 ft

Max. Storage

= 807.19 ft = 83,113 cuft




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 4

DA 1.2

Hydrograph type = SCS Runoff Peak discharge = 100.56 cfsStorm frequency = 2 yrsTime to peak = 716 min Hyd. volume Time interval = 2 min = 205,499 cuftCurve number Drainage area = 27.610 ac= 86 Basin Slope = 0.0 % Hydraulic length = 0 ftTc method Time of conc. (Tc) $= 6.00 \, \text{min}$ = User Distribution Total precip. = 3.60 in= Type II = 484 Storm duration = 24 hrs Shape factor



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

= 82.22 cfs

Hyd. No. 3

DA 2.1

Hydrograph type = SCS Runoff Peak discharge Storm frequency = 2 yrsTime interval = 2 min Drainage area = 23.380 ac Basin Slope = 0.0 % Tc method = User Total precip. = 3.60 inDistribution Storm duration = 24 hrs Shape factor

Time to peak = 716 min

Hyd. volume = 167,383 cuft


Curve number = 85

Hydraulic length = 0 ft

Time of conc. (Tc) = 6.00 min

Distribution = Type II

Shape factor = 484



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Pond No. 3 - Detention Basin #2

Pond Data


Contours -User-defined contour areas. Conic method used for volume calculation. Begining Elevation = 799.00 ft

Stage / Storage Table

Stage (ft)	Elevation (ft)	Contour area (sqft)	Incr. Storage (cuft)	Total storage (cuft)
0.00	799.00	00	0	0
0.01	799.01	100	0	0
1.00	800.00	23,963	8,451	8,451
2.00	801.00	44,503	33,704	42,155
3.00	802.00	70,732	57,108	99,263
4.00	803.00	76,218	73,451	172,713
5.00	804.00	81,851	79,010	251,723
6.00	805.00	87,605	84,703	336,427
7.00	806.00	93,480	90,518	426,944
8.00	807.00	99,469	96,449	523,393

Culvert / Orifice Structures Weir Structures [A] [B] [C] [PrfRsr] [A] [B] [C] [D] 0.00 = 16.00 25.00 2.00 0.00 = 42.00 4.00 0.00 Crest Len (ft) Rise (in) 0.00 0.00 Crest El. (ft) = 805.00 805.75 804.50 0.00 Span (in) = 42.00 4.00 No. Barrels Weir Coeff. = 3.332.60 3.33 3.33 = 799.00 799.00 0.00 0.00 Weir Type Broad Rect Invert El. (ft) 0.00 0.00 Multi-Stage = Yes Yes No Length (ft) = 100.000.00 No 0.00 0.00 n/a Slope (%) = 1.00 = .013 .013 n/a .013 N-Value = 0.60 0.60 0.60 0.60 Exfil.(in/hr) = 0.000 (by Wet area) Orifice Coeff. Multi-Stage = n/aYes No No TW Elev. (ft) = 0.00

Note: Culvert/Orifice outflows are analyzed under inlet (ic) and outlet (oc) control. Weir risers checked for orifice conditions (ic) and submergence (s).



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 5

Thru Detention Basin#2

Hydrograph type Storm frequency = Reservoir

Peak discharge Time to peak = 1.870 cfs = 966 min

Storm frequency Time interval = 2 yrs = 2 min Time to peak Hyd. volume

= 205,540 cuft

Inflow hyd. No.

= 4 - DA 1.2

Max. Elevation


= 802.40 ft

Reservoir name

= Detention Basin #2

Max. Storage

= 128,308 cuft



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Hyd. No. 6DA BYPASS 2.1

<u>Description</u>	<u>A</u>		<u>B</u>		<u>C</u>		<u>Totals</u>
Sheet Flow Manning's n-value Flow length (ft) Two-year 24-hr precip. (in) Land slope (%)	= 0.400 = 100.0 = 3.60 = 5.00		0.011 0.0 0.00 0.00		0.011 0.0 0.00 0.00		
Travel Time (min)	= 14.03	+	0.00	+	0.00	=	14.03
Shallow Concentrated Flow Flow length (ft) Watercourse slope (%) Surface description Average velocity (ft/s)	= 562.00 = 3.02 = Unpaved =2.80	I	0.00 0.00 Paved 0.00		0.00 0.00 Paved 0.00		
Travel Time (min)	= 3.34	+	0.00	+	0.00	=	3.34
Channel Flow X sectional flow area (sqft) Wetted perimeter (ft) Channel slope (%) Manning's n-value Velocity (ft/s)	= 0.00 = 0.00 = 0.00 = 0.015 =0.00		0.00 0.00 0.00 0.015		0.00 0.00 0.00 0.015		
	-0.00		0.00		0.00		
Flow length (ft)	({0})0.0		0.00		0.00		
Flow length (ft) Travel Time (min)		+		+		=	0.00


Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 6

DA BYPASS 2.1

Hydrograph type = SCS Runoff Peak discharge $= 9.445 \, cfs$ Storm frequency = 2 yrs Time to peak = 726 min Time interval = 2 min Hyd. volume = 39,077 cuft Drainage area = 17.410 acCurve number = 61 = 0.0 % Basin Slope Hydraulic length = 0 ftTc method = TR55 Time of conc. (Tc) = 17.40 min Total precip. = 3.60 inDistribution = Type II Storm duration = 24 hrs Shape factor = 484



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Pond No. 7 - Detention Basin #3

Pond Data

Contours -User-defined contour areas. Conic method used for volume calculation. Begining Elevation = 802.00 ft

Stage / Storage Table


Stage (ft)	Elevation (ft)	Contour area (sqft)	Incr. Storage (cuft)	Total storage (cuft)
0.00	802.00	00	0	0
0.01	802.10	100	0	0
1.00	803.00	10,959	3,995	3,995
2.00	804.00	30,577	19,945	23,940
3.00	805.00	39,703	35,037	58,978
4.00	806.00	42,916	41,295	100,272
5.00	807.00	46,186	44,537	144,809
6.00	808.00	49,513	47,835	192,644
7.00	809.00	52,896	51,190	243,834
8.00	810.00	56,335	54,601	298,434
8.50	810.50	58,076	28,599	327,033

Culvert / Orifice Structures

Weir Structures

	[A]	[B]	[C]	[PrfRsr]		[A]	[B]	[C]	[D]
Rise (in)	= 36.00	4.00	0.00	0.00	Crest Len (ft)	= 15.00	40.00	3.00	0.00
Span (in)	= 36.00	4.00	0.00	0.00	Crest El. (ft)	= 808.00	808.50	807.00	0.00
No. Barrels	= 1	1	0	0	Weir Coeff.	= 3.33	2.60	3.33	3.33
Invert El. (ft)	= 802.00	802.00	0.00	0.00	Weir Type	= 1	Broad	Rect	
Length (ft)	= 92.00	0.00	0.00	0.00	Multi-Stage	= Yes	No	Yes	No
Slope (%)	= 0.54	0.00	0.00	n/a					
N-Value	= .013	.013	.013	n/a					
Orifice Coeff.	= 0.60	0.60	0.60	0.60	Exfil.(in/hr)	= 0.000 (by	Wet area)		
Multi-Stage	= n/a	Yes	No	No	TW Elev. (ft)	= 0.00			

Note: Culvert/Orifice outflows are analyzed under inlet (ic) and outlet (oc) control. Weir risers checked for orifice conditions (ic) and submergence (s).



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

= 104,267 cuft

Hyd. No. 7


Thru Detention Basin#3

Hydrograph type = Reservoir Storm frequency = 2 yrs Time interval = 2 min Inflow hyd. No. = 3 - DA 2.1

Reservoir name = Detention Basin #3

Peak discharge = 1.575 cfs Time to peak = 962 min Hyd. volume = 167,392 cuft Max. Elevation = 806.09 ft

Max. Storage




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 9

Outfall 1

Hydrograph type= CombinePeak discharge= 2.938 cfsStorm frequency= 2 yrsTime to peak= 986 minTime interval= 2 minHyd. volume= 334,630 cuftInflow hyds.= 2, 5Contrib. drain. area= 0.000 ac



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 8

Inflow hyds.

Outfall 2


Hydrograph type Storm frequency Time interval = Combine

= 2 yrs = 2 min = 6, 7 Peak discharge Time to peak = 10.95 cfs = 726 min

Hyd. volume

= 206,469 cuft

Contrib. drain. area = 17.410 ac




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 1

DA 1.1

= SCS Runoff Peak discharge = 110.65 cfsHydrograph type Storm frequency Time to peak $= 716 \, \text{min}$ = 10 yrsTime interval = 2 min Hyd. volume = 232,270 cuft = 17.340 acCurve number Drainage area = 86 Basin Slope = 0.0 % Hydraulic length = 0 ftTc method Time of conc. (Tc) = 6.00 min = User = 5.50 inDistribution = Type II Total precip. Shape factor = 484 Storm duration = 24 hrs



Hydrograph Summary Report Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Hyd. N o.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description		
1	SCS Runoff	110.65	2	716	232,270				DA 1.1		
2	Reservoir	1.188	2	1178	232,271	1	809.48	169,351	Thru Detention Basin#1		
3	SCS Runoff	146.12	2	716	304,966				DA 2.1		
4	SCS Runoff	176.19	2	716	369,837				DA 1.2		
5	Reservoir	2.051	2	1150	369,880	4	804.13	263,073	Thru Detention Basin#2		
6	SCS Runoff	31.88	2	726	106,094				DA BYPASS 2.1		
7	Reservoir	6.338	2	790	305,007	3	807.66	176,611	Thru Detention Basin#3		
8	Combine	33.61	2	726	411,102	6, 7			Outfall 2		
Pos	t-Developme	ent Hydraf	low.gpw	1	Return F	Return Period: 10 Year			Thursday, 06 / 25 / 2020		


Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 3

DA 2.1

Hydrograph type = SCS Runoff Peak discharge = 146.12 cfsStorm frequency = 10 yrsTime to peak = 716 min Time interval = 2 min Hvd. volume = 304,966 cuft = 23.380 ac Curve number Drainage area = 85 Basin Slope = 0.0 % Hydraulic length = 0 ftTc method = User Time of conc. (Tc) $= 6.00 \, \text{min}$ Total precip. = 5.50 inDistribution = Type II Storm duration = 24 hrs Shape factor = 484



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 2


Thru Detention Basin#1

Hydrograph type = Reservoir Storm frequency = 10 yrsTime interval = 2 min Inflow hyd. No. = 1 - DA 1.1 Reservoir name

= Detention Basin #1

Peak discharge = 1.188 cfsTime to peak = 1178 min Hyd. volume = 232,271 cuftMax. Elevation $= 809.48 \, \text{ft}$

Max. Storage = 169,351 cuft




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 5

Thru Detention Basin#2

Hydrograph type = Reservoir Peak discharge = 2.051 cfsStorm frequency = 10 yrsTime to peak = 1150 min Time interval = 2 min Hyd. volume = 369,880 cuft Max. Elevation Inflow hyd. No. = 4 - DA 1.2 $= 804.13 \, \text{ft}$ Max. Storage Reservoir name = Detention Basin #2 = 263,073 cuft



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020


Hyd. No. 4

DA 1.2

Hydrograph type = SCS Runoff Storm frequency = 10 yrsTime interval = 2 min = 27.610 acDrainage area Basin Slope = 0.0 % Tc method = User Total precip. = 5.50 inStorm duration = 24 hrs

Peak discharge = 176.19 cfs
Time to peak = 716 min
Hyd. volume = 369,837 cuft
Curve number = 86
Hydraulic length = 0 ft
Time of conc. (Tc) = 6.00 min

Distribution = Type II Shape factor = 484




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 7

Thru Detention Basin#3

Peak discharge Hydrograph type = Reservoir = 6.338 cfsStorm frequency Time to peak = 790 min = 10 yrsTime interval = 2 min Hyd. volume = 305,007 cuftMax. Elevation = 3 - DA 2.1Inflow hvd. No. $= 807.66 \, \text{ft}$ Reservoir name = Detention Basin #3 Max. Storage = 176,611 cuft




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 6

DA BYPASS 2.1

= SCS Runoff Hydrograph type Peak discharge = 31.88 cfsStorm frequency = 10 yrs Time to peak = 726 min Hyd. volume Time interval = 2 min = 106,094 cuftDrainage area = 17.410 acCurve number = 61 Basin Slope = 0.0 % Hydraulic length = 0 ftTc method = TR55 Time of conc. (Tc) $= 17.40 \, \text{min}$ Total precip. = 5.50 inDistribution = Type II Storm duration = 24 hrs Shape factor = 484




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 9

Outfall 1

Hydrograph type = Combine Storm frequency = 10 yrs Time interval = 2 min Inflow hyds. = 2, 5 Peak discharge = 3.541 cfs
Time to peak = 1092 min
Hyd. volume = 602,168 cuft
Contrib. drain. area = 0.000 ac




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 8

Outfall 2

Hydrograph type = Combine Storm frequency = 10 yrs Time interval = 2 min Inflow hyds. = 6, 7 Peak discharge = 33.61 cfs
Time to peak = 726 min
Hyd. volume = 411,102 cuft
Contrib. drain. area = 17.410 ac




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 1

DA 1.1

= SCS Runoff Peak discharge Hydrograph type = 138.14 cfsStorm frequency = 25 yrsTime to peak $= 716 \, \text{min}$ Time interval = 2 min Hyd. volume = 293,981 cuft = 17.340 acCurve number Drainage area = 86 Basin Slope = 0.0 % Hydraulic length = 0 ftTc method = User Time of conc. (Tc) $= 6.00 \, \text{min}$ Total precip. = 6.60 inDistribution = Type II Storm duration = 24 hrs Shape factor = 484



Hydrograph Summary Report Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Hyd. N o.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description		
1	SCS Runoff	138.14	2	716	293,981				DA 1.1		
2	Reservoir	2.475	2	954	294,007	1	810.32	205,343	Thru Detention Basin#1		
3	SCS Runoff	183.24	2	716	387,566				DA 2.1		
4	SCS Runoff	219.96	2	716	468,098				DA 1.2		
5	Reservoir	3.631	2	982	468,118	4	804.87	325,781	Thru Detention Basin#2		
6	SCS Runoff	47.26	2	726	152,760				DA BYPASS 2.1		
7	Reservoir	18.35	2	740	387,585	3	808.20	202,737	Thru Detention Basin#3		
8	Combine	61.80	2	726	540,345	6, 7			Outfall 2		
9	Combine	7.168	2	908	762,119	2, 5,			Outfall 1		
Pos	Post-Development Hydraflow gpw					Return Period: 25 Year			Thursday, 06 / 25 / 2020		
Post-Development Hydraflow.gpw					Return F	Period: 25 Y	′ear	Thursday, (06 / 25 / 2020		


Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 3

DA 2.1

= SCS Runoff Hydrograph type Peak discharge = 183.24 cfsStorm frequency Time to peak = 25 yrs= 716 min Time interval = 2 min Hyd. volume = 387,566 cuft = 23.380 acCurve number Drainage area = 85 Basin Slope = 0.0 %Hydraulic length = 0 ftTc method Time of conc. (Tc) $= 6.00 \, \text{min}$ = User Distribution Total precip. = 6.60 in= Type II = 484 Storm duration = 24 hrs Shape factor



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 2

Thru Detention Basin#1

Hydrograph type = Reservoir Storm frequency = 25 yrsTime interval = 2 min Inflow hyd. No.

Reservoir name

= 1 - DA 1.1


= Detention Basin #1

Peak discharge

 $= 2.475 \, cfs$

Time to peak = 954 min Hyd. volume = 294,007 cuft Max. Elevation $= 810.32 \, ft$

Max. Storage = 205,343 cuft




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 5

Thru Detention Basin#2

Peak discharge = 3.631 cfsHydrograph type = Reservoir Storm frequency = 25 yrsTime to peak = 982 min Hyd. volume Time interval = 2 min = 468,118 cuft Max. Elevation Inflow hyd. No. = 4 - DA 1.2 $= 804.87 \, \text{ft}$ Reservoir name = Detention Basin #2 Max. Storage = 325,781 cuft



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 4

DA 1.2

Hydrograph type = SCS Runoff Storm frequency = 25 yrsTime interval = 2 min Drainage area = 27.610 acBasin Slope = 0.0 % Tc method = User Total precip. = 6.60 inStorm duration = 24 hrs


Peak discharge = 219.96 cfs
Time to peak = 716 min
Hyd. volume = 468,098 cuft
Curve number = 86
Hydraulic length = 0 ft
Time of conc. (Tc) = 6.00 min

= Type II

= 484

Distribution

Shape factor




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 7

Thru Detention Basin#3

Hydrograph type = Reservoir Peak discharge = 18.35 cfsStorm frequency Time to peak = 25 yrs $= 740 \, \text{min}$ Time interval Hyd. volume = 387,585 cuft = 2 min = 3 - DA 2.1Max. Elevation Inflow hyd. No. $= 808.20 \, \text{ft}$ Reservoir name = Detention Basin #3 Max. Storage = 202,737 cuft




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 6

DA BYPASS 2.1

Hydrograph type = SCS Runoff Peak discharge = 47.26 cfsStorm frequency = 25 yrsTime to peak = 726 min Time interval = 2 min Hyd. volume = 152,760 cuftDrainage area = 17.410 acCurve number = 61 Basin Slope = 0.0 % Hydraulic length = 0 ftTime of conc. (Tc) Tc method = TR55 $= 17.40 \, \text{min}$ Total precip. = 6.60 inDistribution = Type II Shape factor Storm duration = 24 hrs = 484




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 9

Outfall 1

Hydrograph type = Combine Storm frequency = 25 yrs Time interval = 2 min Inflow hyds. = 2, 5 Peak discharge = 7.168 cfs
Time to peak = 908 min
Hyd. volume = 762,119 cuft
Contrib. drain. area = 0.000 ac




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 8

Outfall 2

Hydrograph type = Combine Storm frequency = 25 yrs Time interval = 2 min Inflow hyds. = 6, 7 Peak discharge = 61.80 cfs
Time to peak = 726 min
Hyd. volume = 540,345 cuft
Contrib. drain. area = 17.410 ac




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 1

DA 1.1

Hydrograph type = SCS Runoff Peak discharge = 207.53 cfsStorm frequency = 100 yrsTime to peak $= 716 \, \text{min}$ Time interval = 2 min Hyd. volume = 454,032 cuft Drainage area = 17.340 acCurve number = 86 Basin Slope = 0.0 % Hydraulic length = 0 ftTc method Time of conc. (Tc) = User $= 6.00 \, \text{min}$ Total precip. = 9.40 inDistribution = Type II Storm duration = 24 hrs = 484 Shape factor



Hydrograph Summary Report Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description		
1	SCS Runoff	207.53	2	716	454,032				DA 1.1		
2	Reservoir	37.79	2	726	454,050	1	811.14	242,775	Thru Detention Basin#1		
3	SCS Runoff	277.06	2	716	602,339				DA 2.1		
4	SCS Runoff	330.44	2	716	722,942				DA 1.2		
5	Reservoir	36.40	2	736	722,987	4	805.64	394,471	Thru Detention Basin#2		
6	SCS Runoff	91.39	2	724	287,176				DA BYPASS 2.1		
7	Reservoir	159.03	2	722	602,348	3	809.37	262,346	Thru Detention Basin#3		
8	Combine	246.41	2	722	889,524	6, 7			Outfall 2		
9	Combine	72.26	2	728	1,177,037	2, 5,			Outfall 1		
Pos	st-Developme	ent Hydra	low.gpw	,	Return F	Return Period: 100 Year			Thursday, 06 / 25 / 2020		


Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 3

DA 2.1

Hydrograph type = SCS Runoff Peak discharge = 277.06 cfsStorm frequency = 100 yrsTime to peak $= 716 \, \text{min}$ Time interval = 2 min Hyd. volume = 602,339 cuftDrainage area = 23.380 ac Curve number = 85 Basin Slope = 0.0 %Hydraulic length = 0 ftTc method = User Time of conc. (Tc) $= 6.00 \, \text{min}$ Total precip. = 9.40 inDistribution = Type II Storm duration = 24 hrs Shape factor = 484



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 2

Thru Detention Basin#1

Hydrograph type = Reservoir Storm frequency = 100 yrs Time interval = 2 min Inflow hyd. No. = 1 - DA 1.1

= Detention Basin #1

Peak discharge Time to peak Hyd. volume

Max. Elevation


Max. Storage

= 37.79 cfs = 726 min = 454,050 cuft

= 811.14 ft = 242,775 cuft

Storage Indication method used.

Reservoir name



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020


Thursday, 06 / 25 / 2020

Hyd. No. 5

Thru Detention Basin#2

Hydrograph type = Reservoir Peak discharge = 36.40 cfsStorm frequency = 100 yrsTime to peak $= 736 \, \text{min}$ Time interval = 2 min Hyd. volume = 722,987 cuftInflow hyd. No. = 4 - DA 1.2Max. Elevation $= 805.64 \, \mathrm{ft}$ Reservoir name = Detention Basin #2 Max. Storage = 394,471 cuft

Storage Indication method used.




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 4

DA 1.2

Hydrograph type = SCS Runoff Peak discharge = 330.44 cfsStorm frequency = 100 yrsTime to peak $= 716 \, \text{min}$ Time interval = 2 min Hyd. volume = 722,942 cuft Drainage area = 27.610 acCurve number = 86 Hydraulic length Basin Slope = 0.0 %= 0 ftTc method = User Time of conc. (Tc) $= 6.00 \, \text{min}$ Distribution = Type II Total precip. = 9.40 inStorm duration = 24 hrs Shape factor = 484



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020


Thursday, 06 / 25 / 2020

Hyd. No. 7

Thru Detention Basin#3

Hydrograph type = Reservoir Peak discharge = 159.03 cfsStorm frequency = 100 yrsTime to peak = 722 min Hyd. volume Time interval = 2 min = 602,348 cuft= 3 - DA 2.1Inflow hyd. No. Max. Elevation $= 809.37 \, \text{ft}$ Reservoir name = Detention Basin #3 Max. Storage = 262,346 cuft

Storage Indication method used.



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020


Hyd. No. 6

DA BYPASS 2.1

= SCS Runoff Hydrograph type Storm frequency = 100 yrsTime interval = 2 min = 17.410 acDrainage area Basin Slope = 0.0 % Tc method = TR55 = 9.40 inTotal precip. Storm duration = 24 hrs

Peak discharge = 91.39 cfs
Time to peak = 724 min
Hyd. volume = 287,176 cuft
Curve number = 61
Hydraulic length = 0 ft

Time of conc. (Tc) = 17.40 min
Distribution = Type II
Shape factor = 484



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020


Thursday, 06 / 25 / 2020

Hyd. No. 9

Outfall 1

Hydrograph type = Combine Storm frequency = 100 yrs Time interval = 2 min Inflow hyds. = 2, 5 Peak discharge = 72.26 cfs
Time to peak = 728 min
Hyd. volume = 1,177,037 cuft

Contrib. drain. area = 0.000 ac




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Hyd. No. 8

Outfall 2

Hydrograph type = Combine Storm frequency = 100 yrs Time interval = 2 min Inflow hyds. = 6, 7 Peak discharge = 246.41 cfs
Time to peak = 722 min
Hyd. volume = 889,524 cuft
Contrib. drain. area = 17.410 ac



Hydraflow Rainfall Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 06 / 25 / 2020

Return Period	Intensity-Duration-Frequency Equation Coefficients (FHA)									
(Yrs)	В	D	E	(N/A)						
1	0.0000	0.0000	0.0000							
2	69.8703	13.1000	0.8658							
3	0.0000	0.0000	0.0000							
5	79.2597	14.6000	0.8369							
10	88.2351	15.5000	0.8279							
25	102.6072	16.5000	0.8217							
50	114.8193	17.2000	0.8199							
100	127.1596	17.8000	0.8186							

File name: SampleFHA.idf

Intensity = $B / (Tc + D)^E$

Return Period (Yrs)	Intensity Values (in/hr)											
	5 min	10	15	20	25	30	35	40	45	50	55	60
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2	5.69	4.61	3.89	3.38	2.99	2.69	2.44	2.24	2.07	1.93	1.81	1.70
3	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
5	6.57	5.43	4.65	4.08	3.65	3.30	3.02	2.79	2.59	2.42	2.27	2.15
10	7.24	6.04	5.21	4.59	4.12	3.74	3.43	3.17	2.95	2.77	2.60	2.46
25	8.25	6.95	6.03	5.34	4.80	4.38	4.02	3.73	3.48	3.26	3.07	2.91
50	9.04	7.65	6.66	5.92	5.34	4.87	4.49	4.16	3.88	3.65	3.44	3.25
100	9.83	8.36	7.30	6.50	5.87	5.36	4.94	4.59	4.29	4.03	3.80	3.60

Tc = time in minutes. Values may exceed 60.

Two C&D Landfill Expansion Anderson Cnty\Engineering Calculations\Stormwater\Anderson County 24 hr Rainfall.pcp

		R	e (in)					
Storm Distribution	1-yr	2-yr	3-yr	5-yr	10-yr	25-yr	50-yr	100-yr
SCS 24-hour	3.30	3.60	0.00	0.00	5.50	6.60	0.00	9.40
SCS 6-Hr	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Huff-1st	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Huff-2nd	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Huff-3rd	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Huff-4th	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Huff-Indy	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Custom	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

