

# Evaluating Living Shorelines to Inform Regulatory Decision-Making in South Carolina




DNR



**Andrew Tweel**  
Peter Kingsley-Smith  
Denise Sanger  
Sharleen Johnson  
Blaik Keppler  
Michael Hodges  
Benjamin Stone  
Gary Sundin  
Erik Smith

# South Carolina Oyster Restoration and Enhancement (SCORE) Program:

- Creating reefs since 2001.
- 294 individual reefs, 107 sites.
- 4.8 acres of new reef habitat.



**Loose oyster shell**



**Bagged oyster shell**



**Oyster castles**




**Repurposed  
Crab traps**

# Natural Fibers

Curlex Bloc™  
(with shell bolster)

Coir log  
(with shell bolster)



# Wire mesh reefs

**Repurposed crab trap  
(RCT)**



**Manufactured wire reef (MWR)**




# Project Components:

- Create and monitor new experimental sites
  - New materials, new location types
- Monitor existing reef sites
  - Longer time trajectory
- Comprehensive data synthesis and analysis
- Compile guidance document

# South Carolina Oyster Restoration and Enhancement (SCORE) Program:


- Pre-existing sites selected for monitoring for current project.
- Reefs from 0 to 15 years in age.
- Multiple year classes at sites.



# Monitoring of existing reefs

**RCT**

**Bagged  
Shell**



**Age at time  
of monitoring**


Morphology	Dredged	Inside	Outside	Outside- straight	Straight	ICW: no	ICW: yes
Bagged Shell	4	6	14	6	11	28	13
RCTs	1	3	3		2	7	2



**Generally high energy areas**

**Also open bays, not included for existing reefs**

# Locations of newly created living shoreline sites.



# Site Type Categories

## Type A

- Successful bagged shell reef (SCORE) sites.
- Relatively gentle slope.
- Relatively firm sediment.

## Type B

- Environment supports oysters, but previous SCORE reefs were not successful.
- Steep slope or soft sediment.

## Type C

- Physical environment not conducive to oyster-based strategies (e.g., salinity too low, variable)
- Focus is on natural fiber-based approaches.

# Installation of new reefs

Sites		LIVING SHORELINE TREATMENTS							Year
Type	Location	Shell Bags	Bags + pallets	MWR v1	MWR v2	Curlex	Coir -single	Coir -double	
A	Coosaw Cut	1				1	3		2016
	Dataw Is.	1				2	5		2016
	Boy Scout	1				1	3		2016
B	Hobcaw		1	1		1			2016
	Morgan Is.		1	1		1	1		2016
	Bohicket		1	1		1	1		2016
	Dawho		1	1			2		2016
	Abbapoola		1	1			1		2016
	Big Bay		1	1			2		2016
	Awendaw		2	1	1			2	2017
	Orangegroove		2	1	1			2	2017
	Ft Johnson		1	1	1			1	2017
C	Combahee 2					2	4		2016
	Combahee 3					2	4		2016
	Whitehouse					2	4		2017
	Little Dock					1	3		2017


# Assessing Site Characteristics

- Substrate characterization
  - Sediment % silt/clay
  - Sink depth (pluffiness). Ease of measurement.
- Bank slope and bank width
- Water body width (fetch)
- Salinity
- Escarpment height
- Erosion rate (DSAS)
- Geomorphology (outside bend, inside...etc.)
- Vertical placement relative to:
  - Tide frame
  - Marsh edge

# Assessing Treatment Performance

- Did treatment fail?
- Did treatment lose some integrity?
  - Sliding downslope, dislodged, partial sediment smothering
- How well did it perform?
  - Sediment type change
  - Vertical change (sediment build up)
  - Lateral change (marsh expansion or erosion prevention)
  - Oyster coverage

# Monitoring design schematic



Immediately after installation.



Big Bay Creek, July 26<sup>th</sup> 2016

# 3 months after installation And Hurricane Matthew.



Big Bay Creek, October 14<sup>th</sup> 2016

# Coir logs, 32 mo. post-install (after 2 hurricanes)

## Note natural marsh expansion



Big Bay Creek, May 3<sup>rd</sup>, 2019

# 3 months after installation & Hurricane Matthew



Big Bay Creek, October 14<sup>th</sup> 2016

# MWR, 32 months after installation



Big Bay Creek, May 3<sup>rd</sup>, 2019

**Curlex Bloc**

**Coosaw Cut on June 23<sup>rd</sup>, 2016**



August 16, 2016



October 17, 2016



# UAV


## Analysis Points


- Marsh Edge
- High Reef Point

2015 Bagged Shell Reef

Control Site


*Chechessee River*





**Analysis Points**

- Marsh Edge
- High Reef Point
- Higher Elevation
- Lower Elevation




2015 Bagged Shell Reef

Control Site

# Data analysis


- Regression, ANOVA
  - Treatments over time, treatment comparison
- Stepwise multiple regression
  - Isolate site characteristics associated with performance metrics
- PRIMER
  - Look for trends and patterns between sites
- Combined results with existing knowledge base to develop **decision tree** and **tables**

# Results: difference in slope Existing



# Results: difference in accretion

## New builds




**One Year**

1 yr: BS=CL>MWR

2 yr: CL>MWR

**Two Years**



# Results: difference in marsh edge Existing




$p = 0.004$   
Slope = 40 cm/yr

# Results: difference in marsh edge

## New builds



# Results: difference in oyster cover Existing



Bagged Shell

$p = 0.02$   
Slope = 3%/yr


Repurposed Crab Traps

$p = 0.01$   
Slope = 11%/yr

But lack of older data likely biases rate

# Results: difference in oyster cover

## New builds




1 yr: BS>MWR

2 yr: BS=MWR

Site Conditions		Bagged shell	MWR	Coir log
Energy	ICW/dredged	Successful during study. Recommend using extra stakes and checking placement as material may move. Reduced sediment accretion compared to non-ICW.	Successful during study. Recommend using extra stakes and checking placement as material may move. Reduced sediment accretion compared to non-ICW.	Not successful during study. Material moved or degraded quickly.
	Open bay/exposed (wide water width)	Successful during study. Recommend using extra stakes and checking placement as material may move.	Successful during study. Recommend using extra stakes and checking placement as material may move.	Not successful during study. Material moved or degraded quickly.
	Outside bend	Successful during study.	Successful during study.	Successful during study. Lower success rate on outside bend in larger tidal creek or river systems.
	Straight shoreline	Successful during study.	Successful during study.	Successful during study. If low-energy system.
	Inside bend	Successful during study. High sediment accretion potential.	Successful during study. High sediment accretion potential.	Successful during study. High sediment accretion potential.
Salinity	High salinity (>10 ppt) or oysters naturally occur nearby	Successful during study.	Successful during study.	Successful during study.
	Low salinity (<10 ppt) or oysters do not naturally occur nearby	Not successful during study.	Not successful during study.	Successful during study. Only choice tested for non-oyster/low salinity areas.
Sediment Firmness/Composition	High sinkability (>10 cm)	Successful during study. Recommend using pallets. High potential for sediment accretion.	Successful during study. Recommend using deep stakes or extra stakes. High potential for sediment accretion.	Successful during study. Recommend using extra stakes to prevent the log from sliding downslope. High potential for sediment accretion.
	Low sinkability (<10 cm)	Successful during study.	Successful during study.	Successful during study.
	Muddy substrate - pluffy (silt/clay >60-70%)	Successful during study. Recommend using pallets and extra stakes. Increased sediment accretion potential.	Successful during study. Good potential for sediment accretion, but may exhibit reduced oyster growth.	Successful during study.
	Sandy substrate - pluffy (silt/clay <60-70%)	Successful during study.	Successful during study.	Successful during study.
Bank Slope and Width	High slope (>30%)	Not successful during study.	Not successful during study.	Not successful during study.
	Moderate slope (16%-30%)	Not successful during study.	Successful during study. Tested up to 28%.	Successful during study. Avoid in areas >25%.
	Low slope (<16%)	Successful during study. May exhibit greater sediment accretion at slopes >10%.	Successful during study. Well-suited for high slope (tested up to 28%). High accretion potential at higher slopes (>10%).	Successful during study.
	Bank width (marsh to waterline distance)	Successful during study. Performs best at widths <15 ft (5 m).	Successful during study. Performs best at widths <15 ft (5 m).	Successful during study. For range of bank widths, including banks >15 ft (5 m).
High escarpment		Successful during study. More likely to exhibit marsh protection up to 60 cm. Higher than 60 cm uncertain or ineffective.	Successful during study.	Successful during study. Moderate escarpment heights (20-40 cm) associated with increased sediment accretion.

# Decision tree




*Draft version*

# Marsh presence



*Draft version*

# Energy level




*Draft version*

# Energy level

- Coir logs did not perform well at high energy sites (dredged/ICW, outside bend, open bay)
  - 71% failure rate
- High energy sites also tended to be higher salinity sites
- Recommend extra staking for bagged shell or MWR treatments in high energy areas
- Some treatments exhibited reduced sediment accumulation in high energy areas

# Salinity




*Draft version*

# Salinity

- **Low salinity options tested included coir logs and Curlex Bloc**
- **Curlex Bloc failed in 100% of deployments**
- **Coir log was often successful in low energy high salinity areas along with oyster-based methods**
- **Recommend checking adjacent shoreline for oysters. Lowest salinity tested here ~18 ppt**
- **May work as low as 10-15 ppt**

# Bank width



*Draft version*

# Bank width

- Most sites exhibited bank widths  $< 8$  m, but a few very wide banks tested (15+ m)
- Bank widths  $< 5$  m exhibited:
  - Greater silt/clay change (all)
  - Greater sediment accumulation (all)
  - Greatest potential for marsh protection (BS)
  - Greatest oyster coverage after 2 yr (BS/MWR)
  - Consider placement higher in tidal frame/closer to marsh in wide areas

# Slope



*Draft version*

# Bank slope




- Treatment sliding is a concern in soft substrates, recommend extra staking at higher slopes
  - MWR is a lightweight option, easy to adjust
- Higher slopes exhibited greatest elevation gains and shift to fine sediments (BS/coir)
  - Especially with lower placement of treatment in tidal frame
- Higher placement may provide better marsh protection but less oyster growth

# Bank slope

For bagged shell and manufactured wire reefs, movement appears to be a function of slope **and** substrate type

Coir logs exhibited failure in many cases and did not fit this trend.

71% of failures were at high energy sites





# Sink depth

- SCORE program typically uses pallets at softer (pluffy) sites (<~10 cm sink depth)
- Provides firm base, solid structure to stake down
- Recommend extra staking
- High potential for sediment accumulation



# Results: treatment failure

INTEGRITY FAIL	No	Yes (%)
Bagged Shell	13	1 (7)
Coir Logs	17	21 (55)
MWRs	12*	
Curlex Bloc		14 (100)



**Coosaw Cut (after two successive failures)**


# Results: treatment movement

TREATMENT MOVEMENT	No	Yes (%)
Bagged Shell	9	4 (31)
Coir Logs	9	8 (47)
MWRs	10	2 (17)
Curlex Bloc	n.a	n.a.



Abbapoola bagged shell movement

# Decision tree



*Draft version*

# SCDNR field team members:

Trent Austin

Ryan Raiford

Abigail Del Giorno

Holly Kight

Austin Sturkie

Greg Sorg

Grace Smythe

Holly Hillman

Tyler Edwards

Zach Bjur

And others

